

UniCam® Connector, SC, Organizer Pack

CORNING

Corning UniCam® SC connectors offer optical performance in a fast, easy field-termination solution ideal for fiber-to-the-workstation applications where setup and teardown time is critical. The high-precision mechanical splice technology enables fiber optic networks to be installed quickly and cost effectively. Installation of an LC, SC or ST® compatible connector can be accomplished in about 50 seconds to one minute with the UniCam High-Performance Tool Kit.

The lightweight, handheld installation tool and high-performance precision cleaver virtually eliminate human variability during installation, ensuring terminations are right the first time, every time. This kit was designed with consideration for network installers, from the cleaver, with its intuitive, hand-held precision design and dual-clamp precision hold, to the installation tool, with its immediate go/no-go feedback signal indicating proper mating of the field fiber to the fiber stub. Installation is as easy as strip, clean, cleave, cam and crimp, with exceptional optical performance assured. Every UniCam® connector is assured to meet the published specification at the time of installation or Corning will replace it.



Features and Benefits

Performance guaranteed

100 percent yield guarantee

Broad operating temperature range (-40°C to +75°C)

Utility and flexibility

Factory-polished end face

Consistent optical performance

Fast termination and no consumables

Low installation cost

Minimum insertion loss

Optimum optical performance

UniCam® Connector, SC, Organizer Pack

CORNING

Standards

RoHS Free of hazardous substances according to RoHS 2011/65/EU

Approvals and Listings Passed EIA/TIA 568-B.3

Specifications

General Specifications

Keyed (security) No

Product Type Field-Installable Connectors

Technology No-Epoxy/No-Polish

Environmental Conditions

Temperature Range, Operation -40 °C - 75 °C (-40 °F - 167 °F)

Design Connector

Part Number	Connector Type	Ferrule Material	Housing Material	Boot Color	Housing Color
95-000-40-Z	SC	Ceramic	Composite	Beige	Beige
95-000-41-Z	SC	Ceramic	Composite	Beige	Beige
95-050-40-Z	SC	Ceramic	Composite	Black	Black
95-050-41-X-Z	SC	Ceramic	Composite	Aqua	Black

UniCam® Connector, SC, Organizer Pack



Design Connector

Part Number	Connector Type	Ferrule Material	Housing Material	Boot Color	Housing Color
95-050-41-Z	SC	Ceramic	Composite	Black	Black
95-200-41-Z	SC	Composite	Composite	Blue	Blue
95-200-44-Z	SC	Composite	Composite	Green	Green

Optical Specifications Connector

Part Number	Insertion Loss, Max.	Polish	Fiber Category
95-050-40-Z	0.5 dB		50 µm MM (OM2)
95-050-41-Z	0.5 dB		50 µm MM (OM2)
95-050-41-X-Z	0.5 dB		50 µm MM (OM3/OM4)
95-000-40-Z	0.5 dB		62.5 µm MM (OM1)
95-000-41-Z	0.5 dB		62.5 µm MM (OM1)
95-200-41-Z	0.5 dB	UPC	Single-mode (OS2)
95-200-44-Z	0.75 dB	APC	Single-mode (OS2)

Mechanical Specifications - Connector

Durability ≤ 0.2 dB change, 500 rematings, FOTP-21

Nominal Fiber Outer Diameter 125 µm

UniCam® Connector, SC, Organizer Pack



Mechanical Specifications - Connector

Tensile Strength 900 µm Cable

4.9 N (1.1 lb) change ≤ 0.2 dB, FOTP-6

Ordering Information

Part Number	Package Contents
95-000-40-Z	25 connectors, 25 shrouds, 25 boots (900 µm)
95-000-41-Z	25 connectors, 25 shrouds, 25 boots (900 µm)
95-050-40-Z	25 connectors, 25 shrouds, 25 boots (900 µm)
95-050-41-X-Z	25 connectors, 25 shrouds, 25 boots (900 µm)
95-050-41-Z	25 connectors, 25 shrouds, 25 boots (900 µm)
95-200-41-Z	25 connectors, 25 shrouds, 25 boots (900 µm)
<u>95-200-44-Z</u>	Connector, shroud, crimp band, boot (900 µm), boot (3.0 mm)

Shipping Information

Part Number
95-000-40-Z
95-000-41-Z
95-050-40-Z
95-050-41-X-Z

UniCam® Connector, SC, Organizer Pack

CORNING

Part Number

95-050-41-Z

95-200-41-Z

[95-200-44-Z](#)



www.specialized.net

Debbi Kosakowski - National Sales Manager • dkosakowski@specialized.net • 727-515-0911
Eleanor Barszowski - NE Regional Sales Manager • ebarszowski@specialized.net • 484-955-3178
Carolyn Thompson - CSR Midwest/NE • carolyn@specialized.net • 813-295-9889
Becca Bowman - CSR NE/Western • bbowman@specialized.net • 727-412-1591