

Torque Wrenches

- Audible "click" and/or a few degrees of travel provide simple, fast indication of micrometer - accurate torque
- Low friction torque control mechanism produces accurate readings in either direction.
- All torque wrenches have tolerance limits of +/-4% in clockwise (right-hand) setting.
- Two calibration adjustments (major and fine) permit easy and precise torque settings. Most conventional torque wrenches have only one adjustment
- Dual scale models give readings in Inch-Pounds/Newton Meters or Foot-Pounds/Newton Meters.
- Spring-loaded or Twist-Locking collar locks scale on desired reading and remains in locked position. Wrench cannot be left inadvertently unlocked.
- Heavy-Duty, reversible ratchet models have quick-shift lever to allow easy single-hand shifting.
- Always store all adjustable models at their lowest torque setting.



[278X485](#)

[278X773](#)

[278X950](#)

[278X730](#)

[278X306](#)

[278X304](#)

[278X979](#)

[278X957](#)



[278X138](#)

[278X448](#)

P/N

Description

278X485	30150TW10MI - Ratchet Box End Torque Wrench 10mm, 30-150
278X773	40200TW38I - Torque Wrench, 3/8" Dr 40-200 In-Lbs
278X950	30150UTW38I - Torque Wrench, 3/8"Dr 30-150 In-Lbs
278X730	50250TW38I - Torque Wrench, 3/8" Dr 50-250 In-Lbs
278X306	30150UTW38I-LP - 3/8" Low Profile Torque Wrench 30-150 In-Lbs
278X304	30150UTW38I-CW - 3/8" Clockwise Torque Wrench 30-150 In-Lbs
278X979	575TW38F-CW - 3/8" Clockwise Torque Wrench, 5-75 Ft-Lbs
278X984	30150TW716I - TW 7/16" Torque Wrench Ratcheting Head 30-150 In-Lbs
278X138	40200TW38I - CW 3/8" Clockwise Torque Wrench 40-200In-Lbs
278X448	1050TW14I - Insulated Torque Wrench, 1/4" Dr 10-50 In-Lbs
278X957	30150TW38I - 3/8" SQDR Torque Wrench 30-150 In-Lbs.

Torque Socket Kits

The Cementex Specialized Products Socket Sets offer Cementex double-insulated 3/8" square drive 12-point standard socket plus 3" and 6" extensions. All tools are tested to 10,000 volts and rated for use up to 1000 volts AC and 1500 volts DC. The kits comply with ASTM F1505 and IEC 60900 standards and help meet the requirements of OSHA 1910.331-335, NFPA 70E®, and CSA-Z4. They come in 4 zipper bags, made of water-resistant polyester.



SPC990

Insulated 3/8" Sq. Drive SAE & Metric Socket Set, 33-Pc



SPC955

Insulated 3/8" Sq. Drive SAE Socket Set, 17-Piece



SPC975

Insulated 3/8" Sq. Drive Metric Socket Set, 18-Piece