

# UniCam® Connector Standard-Performance Installation Tool Kit

Basic, LC, SC, ST® Compatible

CORNING

The standard UniCam® connector installation tool kit (TKT-UNICAM) is a basic installation tool kit used to terminate all UniCam connector styles (SC, LC and ST compatible connectors). UniCam high-performance multimode connectors (SC, LC and ST compatible) can achieve their optical specifications with the use of this kit. A convenient carrying bag is provided with all the components necessary to terminate UniCam connectors.

The TKT-UNICAM can also be upgraded with a visual fault locator (VFL-350) that provides a visual feedback feature when terminating connectors. The installer can watch an amber glow in the back of the connector tip dim or disappear indicating proper mating of the field fiber to fiber stub within the connector. This is very useful for training new installers and reducing scrap rates.

The standard UniCam® connector installation tool kit (TKT-UNICAM) is a basic installation tool kit used to terminate all UniCam connector styles (LC, SC and ST® compatible connectors). UniCam high-performance multimode connectors (LC, SC and ST compatible) can achieve high-performance with the use of this kit. A convenient carrying bag is provided with all the components necessary to terminate UniCam connectors.

The TKT-UNICAM can also be upgraded with a continuity test set (TEST-UNICAM-CTS) that provides a visual feedback feature when terminating connectors. The installer can watch for a red glow in the back of the connector to dim or disappear indicating that the field fiber is inserted properly into the connector. This is very useful for training new installers and reducing scrap rates.



UniCam Connector Standard Installation Tool Kit | Photo LAN3507

## Features and Benefits

### Terminates single-mode and multimode fibers

Various installation options

### Convenient carrying case

Minimizes setup and teardown time

## Specifications

General Specifications	
Product Type	Connector Tools and Tool Kits
Technology	No-Epoxy/No-Polish
Compatibility	LC, SC and ST® Compatible

# UniCam® Connector Standard-Performance Installation Tool Kit

Basic, LC, SC, ST® Compatible



## Mechanical Characteristics

Dimensions (HxWxD)	24.13 cm x 12.7 cm x 34.5 cm (9.5 in x 5.0 in x 13.58 in)
Weight	2.3 kg (4.95 lb)

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

## Ordering Information

Part Number	TKT-UNICAM
Product Description	Standard Installation Tool Kit for single-fiber UniCam® Connectors, terminates LC, SC and ST® Compatible Connectors; includes FBC-002 basic cleaver, continuity test set (CTS) with adapters; includes all required fiber preparation, cleaning tools and materials
EAN Code	4042673243274

## Shipping Information

Units per Delivery	1/1
Package Contents	UniCam® Installation Tool, Cleaver, Continuity Test Set (CTS) Installation Tool, CTS Adapters, SC UPC/ST® Compatible UPC Jumper, LC UPC/ST Compatible UPC Jumper, Crimp Tool, Gauge Card, Fiber Preparation Tools, Fiber Cleaning Tools



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.