

# Standard LCUPC Duplex SM / Standard LCUPC Duplex SM, SMF Ultra, 2F, Zipcord Riser, Standard Yellow Jacket 1 Meters

CORNING

## Part Number: 040402G5116001M

Cable assemblies are an often overlooked, critical component of your inside plant connectivity portfolio. These products are the component that enables port replication and the ability to cost effectively transmit and receive services between the active electronics and end users. As the industry's leading supplier of cable assemblies, Corning's state-of-the-art manufacturing process ensures reliable connector performance with products that meet or exceed all industry standards for reflectance and insertion loss. Our ability to scale to meet your deployment needs is what sets us apart, along with the highest-quality fiber and factory-tested connectors. All assemblies undergo rigorous performance testing to ensure optimal quality in every connector. Constant process improvements offer a variety of options in fiber, cable, and connector types to meet your network's ever-evolving needs.

If you do not see what you are looking for here, please review the ordering matrix contained in the family specification sheet, or contact Customer Care at 1-800-743-2675.



## Features and Benefits

### State-of-the-art manufacturing processes

Advanced technology results in unsurpassed product consistency and quality

### Global operations

Mitigates trade barriers or supply disruptions

### Flexible design options

Choice of materials for strength elements and fiber properties for various application requirements

### Superior performance testing

Each termination is tested to ensure the highest network performance

# Standard LCUPC Duplex SM / Standard LCUPC Duplex SM, SMF Ultra, 2F, Zipcord Riser, Standard Yellow Jacket 1 Meters



## Specifications

### General Settings

Unit of Measure	Meters
Product Category	2 Fiber

### Furcation A

Outer Diameter	1.6mm
----------------	-------

### Connector A

Connector	LC UPC Dup
Connector Pairing	Duplex
Connector Keying	Non-Keyed
Color	Standard

### Furcation B

Outer Diameter	1.6mm
----------------	-------

### Connector B

Connector	LC UPC Dup
Connector Pairing	Duplex
Connector Keying	Non-Keyed
Color	Standard

# Standard LCUPC Duplex SM / Standard LCUPC Duplex SM, SMF Ultra, 2F, Zipcord Riser, Standard Yellow Jacket 1 Meters

CORNING

## Cable

Fiber Type OS2 Bend-improved SM

Flame Rating Riser

Color Yellow

Length 1

Unit of Measure Meters

Cable Type Zipcord

Fiber Mode Single-Mode



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2020 Corning Optical Communications. All rights reserved.