

# Insulated Nut Drivers

## Insulated Cushion-Grip, Hollow-Shaft Nut Drivers

Additional Features:

- Individually tested to exceed standards.
- Cushion-Grip handles for superior torque and comfort.
- Handle caps are color-coded for easy size identification.
- Insulated, full hollow-shaft permits turning nuts on long screws.



630-5/8-INS

Cat. No.	Color Code	Hex Size	Shank Length	Overall Length	Weight (lbs.)
630-3/16-INS	black	3/16"	3" (76 mm)	6-3/4" (171 mm)	.17
630-1/4-INS	red	1/4"	3" (76 mm)	6-3/4" (171 mm)	.18
630-5/16-INS	yellow	5/16"	3" (76 mm)	6-3/4" (171 mm)	.18
630-11/32-INS	green	11/32"	3" (76 mm)	6-3/4" (171 mm)	.19
630-3/8-INS	blue	3/8"	3" (76 mm)	6-3/4" (171 mm)	.20
630-7/16-INS	brown	7/16"	3" (76 mm)	7-5/16" (186 mm)	.26
630-1/2-INS	red	1/2"	3" (76 mm)	7-5/16" (186 mm)	.28
630-9/16-INS	orange	9/16"	4" (102 mm)	9-3/8" (238 mm)	.40
630-5/8-INS	yellow	5/8"	4" (102 mm)	9-3/8" (238 mm)	.43

Cat. No.	Color Code	Hex Size	Shank Length	Overall Length	Weight (lbs.)
646-3/16-INS	black	3/16"	6" (152mm)	9-3/4" (238 mm)	.22
646-1/4-INS	red	1/4"	6" (152mm)	9-3/4" (238 mm)	.23
646-5/16-INS	yellow	5/16"	6" (152mm)	9-3/4" (238 mm)	.23
646-11/32-INS	green	11/32"	6" (152mm)	9-3/4" (238 mm)	.24
646-3/8-INS	blue	3/8"	6" (152mm)	9-3/4" (238 mm)	.25
646-7/16-INS	brown	7/16"	6" (152mm)	9-3/4" (238 mm)	.31
646-1/2-INS	red	1/2"	6" (152mm)	10-5/16" (262 mm)	.33
646-9/16-INS	orange	9/16"	6" (152mm)	11-3/8" (289 mm)	.45
646-5/8-INS	yellow	5/8"	6" (152mm)	11-3/8" (289 mm)	.48

## Insulated Skinning Knife

### Insulated Cable/Lineman's Skinning Knife

- Individually tested to exceed standards.
- Two layers of insulation provide protection against electric shock.
- Extra-strong construction for line work.
- Tough, tempered-steel blade provides maximum sharpness and durability to withstand frequent cable scoring.
- Rugged insulated handle provides a firm, comfortable grip and has large finger guard.



1570-3LR-INS

Cat. No.	Blade Length	Handle Color	Nominal Overall Length	Weight (lbs.)
1570-3LR-INS	2-1/4" (57 mm)	orange	7-3/4" (197 mm)	.40

## Insulated Screwdriver Sets

### 2-Piece 4" Insulated Screwdriver Set

- Patented Tip-Ident® quickly identifies screwdriver type and tip orientation.
- Individually tested to exceed standards.



33532-INS

Cat. No.	Set Contains	Weight (lbs.)		
33532-INS		.60		
<b>Cat. No.</b>	<b>Description</b>	<b>Shank Tip Width</b>	<b>Shank Length</b>	<b>Overall Length</b>
602-4-INS	round-shank, keystone-tip	1/4" (6 mm)	4" (102 mm)	8-5/16" (211 mm)
603-4-INS	round-shank, profilated Phillips-tip	No. 2	4" (102 mm)	8-5/16" (211 mm)

**⚠WARNING:** Do NOT use to pry or chisel.

All dimensions are in inches and (millimeters).

**⚠WARNING:** Only use tools that are marked with the official international 1000-volt rating symbol shown below, if there is any chance that the tools will make contact with an energized source.



**⚠WARNING:** Whenever possible, always de-energize lines and equipment prior to working on or around them. Klein insulated tools are designed only to reduce the chance of injury where the tool may make contact with an energized source.

**⚠WARNING:** Do NOT touch uninsulated portion of the tool or any conductive object when either might contact an energized source.

**⚠WARNING:** Wear approved eye protection. Always inspect your tools before use. Do not use if orange coating cracks, breaks or becomes damaged. Destroy tool if white layer shows through orange layer.

**⚠WARNING:** Because moisture, films, or other surface contaminants are conductive, Klein insulated tools must be kept clean, dry, and free of any surface contaminants.

