

Compression Tools



C.A.T. / C.A.T. AS / C.A.T. Multimedia Series

Connector Compression Tools



- Spring-loaded split jaw design allows for easy change out of connectors from most connector manufacturers
- Durable cast aluminum body with clear visibility of the connector compression operation
- Simple tool calibration with supplied gauge block (*Not applicable to the FX models*)
- U.S. Patent Nos.: 5,934,137; 5,647,119 & 6,820,326

MODEL	PART #	PLUNGER TIP	PLUNGER TIP COLOR	MATERIAL	CONNECTOR COMPATIBILITY	LENGTH	WEIGHT
Universal	36175-1	Interchangeable	Green	Black-Coated Cast Aluminum	Refer to Chart Below	7.0" (178 mm)	1.0 lb (454 g)
Universal FX	37260	Fixed / Non-Adjustable					
EX	36173	Adjustable/Interchangeable					
IEC/RCA-FX	37765	Fixed / Non-Adjustable	N/A	Black-Coated Cast Aluminum	Two Jaw Sets for Added Versatility; Refer to Chart Below	7.4" (187 mm)	1.1 lb (500 g)
AS	37720	Adjustable/Interchangeable	Green				
AS-FX	37835	Fixed / Non-Adjustable	Black				
AS-EX	37780	Adjustable/Interchangeable					
AS-DIGICON	37785	Adjustable/Interchangeable	Gray				
AS-DIGICON-FX	37845	Fixed / Non-Adjustable					
AS-IEC/RCA-FX	37830	Fixed / Non-Adjustable	N/A				
Multimedia	38855	Fixed / Non-Adjustable	Black	Red-Coated Cast Aluminum	Refer to Chart Below	7.4" (187 mm)	1.1 lb (500 g)

C.A.T. / C.A.T. AS / C.A.T. Multimedia Series Plunger Compatibility Guide

TYPE	CONNECTOR MANUFACTURER	CONNECTOR NAME	C.A.T. SERIES				C.A.T. AS ALL SERIES						C.A.T. MULTIMEDIA
			UNIVERSAL	UNIVERSAL FX	EX	IEC/RCA-FX	AS	AS-FX	AS-EX	AS-DIGICON	AS-DIGICON-FX	AS-IEC/RCA-FX	
59/6	Arris-Digicon	DS & DT™	•	•		•	•	•		•	•	•	•
		DS RCA				•						•	•
	Belden	DS RCA MINI / DS BNC											•
		SNAP-N-SEAL®	•	•		•	•	•					•
	Corning Cabelcon	CX3	•	•		•	•			•	•	•	•
		CX3-IECF / CX3-IECM				•							•
	Corning Gilbert	EFC / F-UE / F-UE-M	•	•		•	•	•		•	•	•	•
		UltraRange®	•	•		•	•	•		•	•	•	•
		UltraShield®	•	•		•	•	•		•	•	•	•
		RCA-UE / RCA-UE-M				•							•
	F-Conn	BNC-UE / BNC-UEM											•
		FS	•	•		•	•	•		•	•	•	•
		FSC				•							•
	Holland	FSU / FS-RCA / FSC-BNC											•
		SLC	•	•		•	•	•		•	•	•	•
	PCT	DRS	•	•		•	•	•	•	•	•	•	•
		DRS-IEF / DRS-IECFM				•							•
	PPC	TRS			•								
		EX			•				•				
		EX XL	•	•		•	•	•		•	•	•	•
CMP		•	•		•	•	•		•	•	•	•	
TFC	CMP-MC							•					
	CMP-RCA / CMP-IEC				•							•	
		QCII	•	•		•	•		•	•	•	•	
7	Arris-Digicon	DS & DT™					•	•		•	•	•	
	Belden	SNAP-N-SEAL®					•	•				•	
	Corning Gilbert	UltraSeal®					•	•				•	
	PPC	EX					•	•	•			•	
	PCT	TRS							•				
11	Arris-Digicon	DS & DT™							•	•		•	
	Belden	SNAP-N-SEAL®					•	•	•			•	
	Corning Cabelcon	CX3					•	•	•			•	
	Corning Gilbert	UltraRange® / UltraSeal® / UltraSeal® 320 QR					•	•	•				•
		URS-MH					•	•		•	•	•	•
	PCT	DRS / DRS-320QR					•	•	•	•	•	•	
PPC	EX / EX320QR					•	•	•	•	•	•		
TFC		QCII					•	•	•	•	•	•	